

FLOIXEM®FIRE

Combustion chamber cleaner for gas and diesel boilers.



Description and applications:

Cleaning and descaling product for gas and oil boilers. Cleans the combustion chamber.

Ready to use, additional dilution or handling not required.

Synergistic combination of dispersants, complexing agents, surfactants and mechanical additives for best performance.

Removes sulphate incrustations reducing rate of corrosion after cleaning

Product characteristics:

Appearance	Transparent liquid
Color	Rojo
pH at 20°C	7.5-9.0
Ignition Point	Non flammable

Data has been gathered in specific bibliography and proprietary test. It is not part necessarily of the technical data.

Properties:

- Eliminates organic deposits and residues from the combustion chamber.
- Special moistening agents to achieve the best penetration of the additives into the residues
- Non corrosive.
- For gas and diesel boilers.
- No storage or transport restrictions
- Additives decompose without leaving residues after use.

Mode of use:

- 1- Turn off the burner.
- 2- Let the boiler reach 50°C or lower.
- 3- Spray the product in the chamber and leave for 15 minutes.
- 4- Turn on the burner and let it reach 80°C for 10 minutes.
- 5- Turn off the heater and allow to cool.
- 6- Remove any remaining residue with a suitable brush. Beware of falling debris that could obstruct certain ducts, in which case remove it using a vacuum cleaner or similar device.

Precautions:

It is a non-flammable and non-corrosive product, so no special precautions are required.

Avoid contact with eyes, in case of splashes wash with plenty of water.

Do not eat or drink, keep out of the reach of children, both the product and its mixtures with water. Store in a clean and well ventilated place, avoid strong heating of the product.

Presentation

		
1 Kg.	15	600
10 Kg.	-	60

One liter container with sprayer included.